

EXPLORER 710

High-Speed, Portable BGAN Terminal

Connecting





EXPLORER 710

High-Speed, Portable BGAN Terminal

Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

Smallest and Lightest

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



Specifications

| Specifications | |
|------------------------------|----------------------------------|
| Dimensions | |
| Total H / W / D: | 332 / 279 / 54 mm |
| | 13.07 / 10.98 / 2.13 inches |
| Total weight: | 3.5 kg / 7.7 lbs (incl. battery) |
| Antenna: | 1.9 kg / 4.2 lbs |
| Transceiver (incl. battery): | 1.6 kg / 3.5 lbs |
| | |

4 kbps AMBE+2

| G | 0 | bal | Services |
|---|---|-----|----------|
| | ٧ | oic | e: |

| Premium voice: | 3.1 kHz audio, 64 kbps |
|----------------------|---------------------------------|
| Standard IP: | Up to 492 kbps |
| Streaming IP: | 32, 64, 128 kbps |
| | (256 kbps & BGAN X-Stream) |
| HDR Streaming: | Min. 600 kbps |
| | Min. 300 kbps (Half-channel |
| HDR) | |
| ISDN: | UDI 64 kbps / RDI 56 kbps |
| SMS: | Not supported |
| nmarsat frequencies: | 1518.0 - 1525.0 MHz (Rx) (EMEA) |

1525.0 - 1559.0 MHz (Rx) 1626.5 - 1660.5 MHz (Tx) 1668.0 - 1675.0 MHz (Tx) (EMEA)

EIRP: 20dBW ±1dB

User Interface: PMOLED Display, 5 navigation keys,

Audio and LCD pointing aids and LED

indicator, Compass

Languages: UK, FR, DE, ES, RU and CN

Approvals: Inmarsat Class 1 Type Approval at launch
CE & FCC at launch. Other approvals TBC



Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

Interfaces

| 1 x Analogue RJ-11 | phone/fax interfaces |
|--------------------|----------------------|
|--------------------|----------------------|

2 x LAN (RJ-45) interface

Power over Ethernet: PoE Cl. 2 on one RJ-45 interface
Max. cable length: 100m / 328ft (Cat5 UTP)

1 x USB host interface 2.0 (host), Charging up to 2A

1 x ISDN interface

Connector type: RJ-45

Max. units per port: 8, max. total power supplied 1W

1 x Transceiver / Antenna interface Connector type: TNC-TN

Max. cable loss: 1.4 / 20dB @ 1.5GHz

1 x BGAN SIM-Card slots

WLAN Access Point

Standard: IEEE 802.11 b/g

Environmental conditions

Temperature

Operational (ambient): -25°C to $+55^{\circ}\text{C}$ / -13°F to $+131^{\circ}\text{F}$ Storage (excl. battery): -40°C to $+80^{\circ}\text{C}$ / -40°F to $+176^{\circ}\text{F}$

Battery storage temperature

1 month: -20°C to +60°C / -4°F to +140°F 3 months: -20°C to +45°C / -4°F to +113°F 1 year: -20°C to +20°C / -4°F to +68°F

Water and dust: Transceiver: IP52 / Antenna: IP66

Relative humidity: 95% non-condensing at +40°C / +104°F

Power

DC input range: 10-32VDC

Power consumption

Intelligent Power Management 65W (max.)

AC/DC power supply

Input: 100-240VAC, 47-63Hz, 65W

Output: 19VDC

Connector type: 2.5 / 5.5 mm power jack

Battery: Lithium ion, rechargeable

Stand-by time: 36 hours

Transmit time, max.: 2h30m @ 144 kbps

(25°C / 77°F) 1h30m @ 650 kbps Receive time, max.: 3h30m @ 492 kbps



Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

Other features

Built-in SIP server

Embedded Webserver

Advanced Router with admin control

Wireless Access Point

Battery hot-swap and Built-in BGAN bonding Remote activation and remote management

EXPLORER Connect App for IOS and Android:

Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.

EXPLORER Cellular Modem for USB:

With the EXPLORER LTE Modem you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices.

Package

EXPLORER 710 Transceiver & Antenna incl. rechargeable lithium ion battery, Antenna cable, 2m ISDN/LAN cable, 115/230VAC power supply, Quick start guide.

Accessories

| 403720B-100 | EXPLORER 710 Antenna |
|---------------|-----------------------------|
| 403686G | Lithium Ion Battery |
| 403720B-010 | Battery Hot Swap Cable |
| 403682P | 100-240V AC/DC Power Supply |
| 403650A-009 | Car Charger Cable |
| 403670A-00500 | IP Handset incl. Cradle |
| 403650A-921 | Pole Mount Kit |
| 403720B-942 | 10m Antenna Cable |
| 403720B-945 | 30m Antenna Cable |
| 403720B-947 | 50m Antenna Cable |
| 403720B-953 | 80m Antenna Cable |
| 403756A-0500 | EXPLORER Cellular USB Modem |

Product number

403720B-00500 EXPLORER 710 Terminal

For further information please contact: satcom.land@cobhamsatcom.com